



HIRTH



Order
Request

Air-cooled single-cylinder engines

Enginetype:

- | | | | |
|--------|--|--|--------------------------|
| F33 A | | slide carburettor, 18,1 kW (24,6 HP) at 6000 rpm | <input type="checkbox"/> |
| F33 B | | diaphragm carburettor, 18,1 kW (24,6 HP) at 6200 rpm | <input type="checkbox"/> |
| F33 AS | | slide carburettor, 20,6 kW (28 HP) at 6500 rpm | <input type="checkbox"/> |
| F33 BS | | diaphragm carburettor, 20,6 kW (28 HP) at 6500 rpm | <input type="checkbox"/> |
| F33 ES | | Injection, 20,6 kW (28 HP) at 6500 rpm | <input type="checkbox"/> |
| F 36 | | diaphragm carburettor, 11 kW (14,9 HP) at 6000 rpm | <input type="checkbox"/> |

Quantity: _____

Please use a separate form for each type of engine and specification (e.g. if you order two or more engines with different options on the next page). Take price for standard engine, the options and the accessories from our present price list.

Client data:

Name: _____

Fon: _____

Company: _____

Fax: _____

Address: _____

Mail: _____

Country/City: _____



Options

Ignition: (only engine F33)

single ignition	<input type="checkbox"/>
dual ignition	<input type="checkbox"/>

Starter arrangement: (only in combination with gear box G33/G36)

with recoil starter (series)	<input type="checkbox"/>
with recoil and electric starter (inclusive starter relay)	<input type="checkbox"/>

Extras:

Generator (50 W) with regulator (included with injection, only F33)	<input type="checkbox"/>
Four-point mounting at ignition side for mounting at fire wall (inclusive 4 rubber dampers, not in combination with fan cooling, only F33)	<input type="checkbox"/>
fan cooling (not in combination with four-point mounting or cylinderhead MAXIMO on F33)	<input type="checkbox"/>
cylinder head MAXIMO (not in combination with fan cooling, only F33)	<input type="checkbox"/>

belt drive G33/G36:

reduction gear ratio	1,8:1 <input type="checkbox"/>	2,2:1 <input type="checkbox"/>	2,5:1 <input type="checkbox"/>
Arrangement of the belt drive	standing <input type="checkbox"/> / <input type="checkbox"/> hanging		

Accessories

Accessories:			Quantity:
BlueMax 2-stroke Oil	up to mixture ratio 1:100, notice technical description		←
	1 liter: _____	5 liter: _____	
Tachometer	digital, rectangular with operation hour meter		_____
Fuel pressure monitor			_____
Engine mounting	tear-off proof, 4xM8		_____
Fuel filter			_____
Primer pump			_____
Propeller	Göbler-Hirthmotoren recommends „Helix“: Info@helix-propeller.de Information on www.helix-propeller.de		
Temperature monitoring	analog, Ø52mm round with one display for cylinder head and one display for exhaust gas temperature, complete with sensors and cables		_____
Ignition switch	only for engine F33		_____

Special request:

(must be arranged with technical department first)

In delivery included:

fuel pump
air filter
one exhaust system

In the following we would like to ask you for some information on the planned use of the engine:

Engine use (e.g. type of aircraft):

Mounting (push or pull version, upside down, vertical,...):

Additional notes (e.g. type of prop):

place/date

signatur/company stamp

Thank you for your order or request, we will send you our confirmation within short time. Please mark on the first page if this is an order or a request.

Delivery time

On account of the job-oriented production the delivery time for standard engines is 4-6 weeks and for special constructions possibly longer.

If you have any questions please feel free to contact us at the numbers listed below. If you have questions to the sale, please contact the following number: : 07144/8551-12.

